


HIPAR-100

OUTDOOR LED PAR CAN RGBWA

Item ref: 154.323UK

User Manual



Caution: Please read this manual carefully before operating
Damage caused by misuse is not covered by the warranty

Introduction

Thank you for your purchase of the QTX HIPAR-100 outdoor LED PAR light. This fixture has been designed to provide powerful and colourful light coverage to a wide area for indoor or outdoor areas. Please read and keep this manual for reference to gain the best results from this product and avoid damage through misuse.

SAFETY SYMBOL AND MESSAGE CONVENTIONS



CAUTION
RISK OF ELECTRIC SHOCK
DO NOT OPEN

AVIS
RISQUE DE CHOC ELECTRIQUE
NE PAS OUVRIR



This symbol indicates that dangerous voltage constituting a risk of electric shock is present within this unit



This symbol indicates that there are important operating and maintenance instructions in the literature accompanying this unit.

Warning

To prevent the risk of fire or electric shock, ensure all power connections are watertight.
No user serviceable parts inside – Do not open the case – refer all servicing to qualified service personnel.

Safety

Check for correct mains voltage and condition of power lead before connecting to a power outlet.

Placement

- Use the included dual mounting bracket to fix to a stand/truss or free-standing on a stable surface
- Use secondary safety fixings if mounting overhead.
- Ensure adequate airflow around the fixture housings
- Ensure adequate access to controls and connections

Cleaning


- Use a soft cloth with a neutral detergent to clean the casing as required
- Do not use strong solvents for cleaning the unit

In the box

Please open the package carefully and check that all contents are present and in good condition.
Contact your retailer if any part is missing or broken.

- HIPAR-100 LED PAR can
- Dual mounting bracket
- UK mains plug to waterproof socket lead
- DMX XLR plug to waterproof socket lead

Rear panel



Installation

The HIPAR-100 is supplied with a dual hanging bracket, which can also be used as a free-standing support.

When installing the fixture, ensure all fixings are secure, controls and connections are accessible and allow enough space for air to circulate around the housing. Do not aim directly in line of sight or very close to people where the extremely bright output of the fixture may be harmful to eyesight.

The HIPAR-100 is IP65 weatherproof and all electrical connections are hard-wired with waterproof connectors. An XLR to waterproof connector is provided for adapting the DMX input lead to a standard DMX signal input. A mains plug to waterproof connector is provided to adapt the power input lead to a standard mains supply.

Connect the waterproof connectors securely, ensuring that the notches are aligned for correct polarity. The waterproof plugs have a threaded collar which must be fully tightened onto the waterproof socket.

The HIPAR-100 also has DMX through and power through leads for connecting onto further HIPAR cans in a daisy-chain manner. Ensure that the mains power supply is capable of the total load of all cans connected.

Setting up

Check all connections are properly made and power up the HIPAR-100 can. The LED display will light and show the current mode or status.

Use the control panel keys to adjust the stand-alone or DMX control settings.

Press MENU to step through the menu options and press ENTER when you reach the required page. Press UP and DOWN keys to adjust the value of the parameter and press ENTER again to confirm. Press MENU again to go back to stepping through menu options.

Please see the table on the following page for the full list of menu options.

Onboard Menu

Display	Press Enter to set value Press Enter again to confirm	Description
<i>Addr</i>	<i>A001 - A512</i>	DMX start address
<i>Chid</i>	<i>5Ch - 9Ch</i>	DMX channel mode – 5 or 9 channels
<i>FAIL</i>	<i>d512 - MASTER - SLAVE</i>	Master/Slave/DMX mode (FAIL means no Master/Slave)
<i>rxxx</i>	<i>r000 - r255</i>	Manual colour red level 0-100%
<i>gxxx</i>	<i>g000 - g255</i>	Manual colour green level 0-100%
<i>bxxx</i>	<i>b000 - b255</i>	Manual colour blue level 0-100%
<i>wxxx</i>	<i>w000 - w255</i>	Manual colour white level 0-100%
<i>Axxx</i>	<i>A000 - A255</i>	Manual colour amber level 0-100%
<i>mode</i>	<i>Sxxx</i> Enter to set <i>S000 - S999</i>	Sound activated colour change (00 - 99= mic sensitivity)
	<i>Cxxx</i> Enter to set <i>C001 - C015</i>	Static colour (01 - 15 = colour selection)
	<i>Axxx</i> Enter to set <i>A000 - A999</i>	Auto colour jump program (00 - 99= speed)
	<i>FAxx</i> Enter to set <i>FA00 - FA99</i>	Auto colour scroll program (00 - 99= speed)
<i>Stro</i>	<i>St00 - St99</i>	Strobe (00 = off, 01 - 99= speed)

Standalone operation

To operate the HIPAR-100 in standalone (autonomous) mode, navigate to *FAIL* and select Master mode. Sound-activated, Static colour, Auto, Fade & Strobe modes described above will operate without DMX control.

To control further HIPAR cans in master-slave mode, connect the DMX through from a master HIPAR-100 in standalone mode to the DMX input of a "slave" HIPAR can that is set to Slave mode under the *FAIL* menu. Further HIPAR cans set to Slave mode may be connected from DMX through to DMX input in a daisy chain.

If the strobe setting is *St01 - St99*, a flashing strobe effect will be applied to the Auto program (slow to fast)

For custom static colours, adjusting the values of *rxxx*, *gxxx*, *bxxx*, *wxxx* and *Axxx* gives a manual colour mix.

DMX operation

The HIPAR-100 is compatible with standard DMX512 control.

Connect the supplied XLR plug to waterproof socket lead to the DMX input lead of the first HIPAR can in line to be controlled. Connect further HIPAR cans from the DMX through of the first can to the DMX input of the second can and DMX through of the second can to the DMX input of the third can etc. until all HIPAR cans are connected in a daisy-chain.

Connect the XLR plug to a DMX controller, ensuring that this connection is protected from the elements. (the XLR plug is not a waterproof connector)

The HIPAR-100 has either 5 or 9 DMX channels as described in the tables on the following pages. Set the DMX value to the required start address via the control panel and this will become the DMX address of channel 1.

To select the DMX channel mode, step through the onboard menu to *Chan* and press ENTER to select either *5Ch* for 5-channel mode or *9Ch* for 9-channel mode.

DMX Channels – 5 Channel Mode

Ch.1	000 - 255	Red level 0-100%
Ch.2	000 - 255	Green level 0-100%
Ch.3	000 - 255	Blue level 0-100%
Ch.4	000 - 255	White level 0-100%
Ch.5	000 - 255	Amber level 0-100%

5-channel DMX mode gives straightforward dimming for individual colour components.

DMX Channels – 9 Channel Mode

Ch.1	000 - 255	Master dimmer level 0-100%
Ch.2	000	Strobe effect off
	001 - 255	Strobe effect speed slow to fast
Ch.3	000 - 010	Macro function off
	011 - 095	Macro - Static colour
	096 - 177	Macro - Colour change
	178 - 255	Macro - Colour scroll
Ch.4	000 - 255	Macro speed 0-100% / Static colour select
Ch.5	000 - 255	Red level 0-100%
Ch.6	000 - 255	Green level 0-100%
Ch.7	000 - 255	Blue level 0-100%
Ch.8	000 - 255	White level 0-100%
Ch.9	000 - 255	Amber level 0-100%

In 9-channel mode, Ch.1 master dimmer setting affects the overall output in any mode.

A custom static colour can be mixed manually on channels 5 to 9 and strobe setting via channel 2.

Macro settings are similar in operation to the stand-alone auto settings with preset static colour, colour-change and colour-scroll programs all accessible from the setting of channel 3.

The speed of the selected effect (macro) is determined by the setting of channel 4.

Specifications

Power supply	110-240Vac, 50/60Hz
IP rating	IP65
Modes	Auto, sound-activated, master/slave, DMX512
Connections	Power in, power out, DMX in, DMX out
Power consumption max.	100W
LED: quantity	7
LED: type	15W RGBWA (5-in-1)
DMX channels	5 or 9
Beam angle	45°
Dimensions	223 x 210 x 178mm
Weight	3.14kg



This product is classed as Electrical or Electronic equipment and should not be disposed with other household or commercial waste at the end of its useful life. The goods must be disposed of according to your local council guidelines.

Errors and omissions excepted.

Copyright© 2021 AVSL Group Ltd, Unit 2 Bridgewater Park,
Taylor Road, Trafford Park, Manchester. M41 7JQ.

AVSL (Europe) Ltd, Unit 3D North Point House,
North Point Bus. Park, New Mallow Road, Cork, Ireland.